



## T8 LEDQUICK-KIT 2FT



### PRODUCT DESCRIPTION

LEDQuick-Kit is a quick, inexpensive and versatile way to retrofit existing fluorescent fixtures without worrying about ballast compatibility or existing socket issues. Our 0-10V DC dimmable LED driver and driver-less LED tubes provide an alternative to LED T8 tubes and LED retrofit kits. These can be used in troffers, strips, surface-mount wraps, stairwell fixtures and more.

### Ordering Information

Example: T810D40EX1G-FW06

Size	Watts	Dimmable	CCT	One Driver with Tubes	Cap	Lens Type	Lens Type
T8	10 - 10W/ Tube	D - 0-10V dimmable	35 - 3500K 40 - 4000K	<b>EX1</b> - one driver with one tube  <b>EX2</b> - one driver with two tube  <b>EX3</b> - one driver with three tube  <b>EX4</b> - one driver with four tube	G - G13	FW - Frost White	06 - 2FT

\* Special Order-Ask Customer Service for Details.

### SPECIFICATION

Tube System	1-Tube system	2-Tube system	3-Tube system	4-Tube system
Voltage	120-277VAC	120-277VAC	120-277VAC	120-277VAC
Power	10W	20W	30W	40W
Color Temperature	3500K/4000K	3500K/4000K	3500K/4000K	3500K/4000K
Power Factor	0.95	0.95	0.95	0.95
Lumen Output	1300lm(One lamp)	2600lm(Two lamps)	3900lm(Three lamps)	5200lm(Four lamps)
LPW	130	130	130	130
CRI	Ra>80	Ra>80	Ra>80	Ra>80
Beam Angle	120°	120°	120°	120°
Harmonic Distortion	<20%	<20%	<20%	<20%
Base Type	G13 Bi-Pin	G13 Bi-Pin/D shape	G13 Bi-Pin/D shape	G13 Bi-Pin/D shape
Life Time	50000H	50000H	50000H	50000H
Operating Temperature	-4°F~113°F	-4°F~113°F	-4°F~113°F	-4°F~113°F
Operation Environment	Indoor	Indoor	Indoor	Indoor
Dimension(L-W-H)	Φ1" *23.88"	Φ1" *23.88"	Φ1" *23.88"	Φ1" *23.88"
Weig (lbs)	0.675lb	1.9lb	2.7lb	3.13lb
Standard	UL/FCC/RoHS/DLC	UL/FCC/RoHS/ DLC	UL/FCC/RoHS/ DLC	UL/FCC/RoHS/ DLC

### PERFORMANCE

CRI

80

CCT

3500K, 4000K

Dimming

0-10V Dimming Standard

Working Temperature

-4°F - 113°F

Certifications

- cULus Conforms to  
UL Std. 1598 & 1598C  
Cert. to CSA Std. C22.2  
No.250.0 & 250.1
- DLC Listed
- RoHs compliant



## T8 LEDQUICK-KIT 3FT



## PRODUCT DESCRIPTION

LEDQuick-Kit is a quick, inexpensive and versatile way to retrofit existing fluorescent fixtures without worrying about ballast compatibility or existing socket issues. Our 0-10V DC dimmable LED driver and driver-less LED tubes provide an alternative to LED T8 tubes and LED retrofit kits. These can be used in troffers, strips, surface-mount wraps, stairwell fixtures and more.

## Ordering Information

Example: T812D40EX1G-FW09

Size	Watts	Dimmable	CCT	One Driver with Tubes	Cap	Lens Type	Lens Type
T8	12- 12W/ Tube	D - 0-10V dimmable	40 - 4000K	<b>EX1</b> - one driver with one tube  <b>EX2</b> - one driver with two tube  <b>EX3</b> - one driver with three tube  <b>EX4</b> - one driver with four tube	G - G13	FW - Frost White	09 - 3FT

\* Special Order-Ask Customer Service for Details.

## SPECIFICATION

Tube System	1-Tube system	2-Tube system	3-Tube system	4-Tube system
Voltage	120-277VAC	120-277VAC	120-277VAC	120-277VAC
Power	12W	24W	36W	48W
Color Temperature	4000K	4000K	4000K	4000K
Power Factor	0.95	0.95	0.95	0.95
Lumen Output	1560lm(One lamp)	3120lm(Two lamps)	4680lm(Three lamps)	6240lm(Four lamps)
LPW	130	130	130	130
CRI	Ra>80	Ra>80	Ra>80	Ra>80
Beam Angle	120°	120°	120°	120°
Harmonic Distortion	<20%	<20%	<20%	<20%
Base Type	G13 Bi-Pin	G13 Bi-Pin/D shape	G13 Bi-Pin/D shape	G13 Bi-Pin/D shape
Life Time	50000H	50000H	50000H	50000H
Operating Temperature	-4°F~113°F	-4°F~113°F	-4°F~113°F	-4°F~113°F
Operation Environment	Indoor	Indoor	Indoor	Indoor
Dimension(L-W-H)	Φ1" *35.4"	Φ1" *35.4"	Φ1" *35.4"	Φ1" *35.4"
Weig (lbs)	0.75lb	2.0lb	2.9lb	3.5lb
Standard	UL/FCC/RoHS	UL/FCC/RoHS	UL/FCC/RoHS	UL/FCC/RoHS

## PERFORMANCE

CRI

80

CCT

4000K

Dimming

0-10V Dimming Standard

Working Temperature

-4°F - 113°F

Certifications

- cULus Conforms to  
UL Std. 1598 & 1598C  
Cert. to CSA Std. C22.2  
No.250.0 & 250.1
- RoHs compliant



## T8 LEDQUICK-KIT 4FT



## PRODUCT DESCRIPTION

LEDQuick-Kit is a quick, inexpensive and versatile way to retrofit existing fluorescent fixtures without worrying about ballast compatibility or existing socket issues. Our 0-10V DC dimmable LED driver and driver-less LED tubes provide an alternative to LED T8 tubes and LED retrofit kits. These can be used in troffers, strips, surface-mount wraps, stairwell fixtures and more.

## Ordering Information

Example: T815D40EX1G-FW12

Size	Watts	Dimmable	CCT	One Driver with Tubes	Cap	Lens Type	Length
T8	15 - 15W/ Tube	D - 0-10V dimmable	35 - 3500K 40 - 4000K	<b>EX1</b> - one driver with one tube  <b>EX2</b> - one driver with two tube  <b>EX3</b> - one driver with three tube  <b>EX4</b> - one driver with four tube	G - G13	FW - Frost White	12 - 4FT

\* Special Order-Ask Customer Service for Details.

## SPECIFICATION

Tube System	1-Tube system	2-Tube system	3-Tube system	4-Tube system
Voltage	120-277VAC	120-277VAC	120-277VAC	120-277VAC
Power	15W	30W	45W	60W
Color Temperature	3500K/4000K	3500K/4000K	3500K/4000K	3500K/4000K
Power Factor	0.95	0.95	0.95	0.95
Lumen Output	1950lm(One lamp)	3900lm(Two lamps)	5850lm(Three lamps)	7800lm( Four lamps)
LPW	130	130	130	130
CRI	Ra>80	Ra>80	Ra>80	Ra>80
Beam Angle	120°	120°	120°	120°
Harmonic Distortion	<20%	<20%	<20%	<20%
Base Type	G13 Bi-Pin	G13 Bi-Pin/D shape	G13 Bi-Pin/D shape	G13 Bi-Pin/D shape
Life Time	50000H	50000H	50000H	50000H
Operating Temperature	-4°F~113°F	-4°F~113°F	-4°F~113°F	-4°F~113°F
Operation Environment	Indoor	Indoor	Indoor	Indoor
Dimension(L-W-H)	Φ1" *47.76"	Φ1" *47.76"	Φ1" *47.76"	Φ1" *47.76"
Weig (lbs)	0.95lb	2.2lb	3.5lb	4.8lb
Standard	UL/FCC/RoHS/DLC	UL/FCC/RoHS/ DLC	UL/FCC/RoHS/ DLC	UL/FCC/RoHS/ DLC

## PERFORMANCE

CRI

80

CCT

3500K, 4000K

Dimming

0-10V Dimming Standard

Working Temperature

-4°F - 113°F

Certifications

- cULus Conforms to  
UL Std. 1598 & 1598C  
Cert. to CSA Std. C22.2  
No.250.0 & 250.1
- DLC listed
- RoHs compliant

Ref#: 20200618