

Floodlight Summary:

Report based on lamp delivering 1000 lumens.


Maximum Intensity		776.2 cd per klm.
(Luminaire orientation as tested.)		0.0 degrees vertical
		0.0 degrees horizontal
Beam Spread	At 10% of Imax	95.9V x 128.1H
	At 50% of Imax	56.1V x 106.1H
	At 90% of Imax	9.4V x 86.3H
Beam Flux	Total	1000.0 lumens per klm.
	To 10% of Imax	955.4 lumens per klm.
	To 50% of Imax	501.9 lumens per klm.
	To 90% of Imax	48.9 lumens per klm.
Upward LOR		0.7 %
Downward LOR		99.3 %
Luminaire Efficiency (Light Output Ratio)		100.0 %

H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:28.9DEG
Operators:07
Test Date:2017-08-04

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.286
Humidity:54.0%
Test Distance:6.325m [K=1.0000]
Remarks:

LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:120.3V I:0.2117A P:25.31W PF:0.9936 Lamp Flux:2795.11x1 lm		
NAME: 投光灯具	TYPE:FLB	WEIGHT:
SPEC.:2002/1000WHQI	DIM.:	SERIAL No.:
MFR.: Above All Lighting	SUR.:	PROTECTION ANGLE:



DATA OF LAMP		Eff:110.43lm/W	
MODEL	10967-SWP25401-A	Imax(cd)	2170
NOMINAL POWER(W)	25	AVAILABILITY(%)	95.5
RATED VOLTAGE(V)	120	Avai. FLUX(lm)	2670
NOMINAL FLUX(lm)	2795.11	LOR(%)	100.0
LAMPS INSIDE	1	TOTAL FLUX(lm)	2795
TEST VOLTAGE(V)	120	θ @50% (H,V)	106,56DEG

VERTICAL (DEG)	AREA FLUX DIAGRAM																UNIT:lm		Φ t	Φ a
	0.00	0.00	0.00	0.00	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.00	0.00	0.00	0.11	0.00
90	0.00	0.00	0.01	0.04	0.11	0.08	0.12	0.28	0.30	0.16	0.08	0.05	0.04	0.03	0.02	0.01	0.00	0.00	1.33	0.00
80	0.00	0.01	0.04	0.18	0.33	0.27	0.68	1.27	1.47	1.42	1.09	0.45	0.20	0.26	0.12	0.02	0.01	0.00	7.82	0.00
70	0.00	0.02	0.06	0.18	0.39	0.48	1.03	1.60	2.23	2.18	1.71	1.06	0.41	0.40	0.28	0.06	0.01	0.00	12.1	0.00
60	0.00	0.02	0.08	0.34	1.76	3.17	3.45	3.93	3.85	2.94	2.23	1.41	0.85	0.61	0.30	0.07	0.01	0.00	25.0	5.73
50	0.00	0.03	0.29	1.78	9.40	15.1	16.9	17.7	17.4	12.4	10.3	8.62	6.42	3.75	0.69	0.09	0.02	0.00	121	112
40	0.00	0.05	0.76	4.44	15.3	25.6	26.1	26.4	27.2	25.9	24.4	22.4	20.0	12.3	2.83	0.26	0.02	0.00	234	230
30	0.00	0.07	1.10	6.28	17.5	28.2	28.0	28.4	28.9	28.7	27.6	27.1	26.7	17.2	5.09	0.65	0.04	0.00	271	268
20	0.00	0.08	1.23	7.35	18.4	28.8	29.3	30.6	30.4	29.9	29.7	29.1	27.7	18.2	6.05	0.93	0.05	0.00	288	284
10	0.00	0.08	1.30	7.32	18.8	28.6	30.5	31.0	30.5	30.7	31.4	30.1	28.4	18.3	6.08	1.06	0.06	0.00	294	290
0	0.00	0.07	1.23	6.65	20.1	31.7	32.9	31.9	31.8	31.8	32.0	32.3	30.4	18.3	5.43	1.03	0.05	0.00	308	304
-10	0.00	0.05	0.93	6.09	22.7	41.7	45.1	45.1	45.9	46.4	45.5	45.5	40.6	19.3	4.27	0.77	0.04	0.00	410	406
-20	0.00	0.03	0.53	4.23	20.0	44.0	51.4	53.0	55.3	55.4	53.9	53.9	41.8	15.4	2.57	0.36	0.03	0.00	452	448
-30	0.00	0.02	0.25	2.12	10.9	26.7	34.3	36.0	36.6	34.0	32.7	31.1	22.2	7.36	1.29	0.14	0.02	0.00	276	271
-40	0.00	0.01	0.09	0.82	2.84	7.08	9.29	10.4	10.0	7.80	7.05	6.54	4.78	1.82	0.51	0.05	0.01	0.00	69.1	52.2
-50	0.00	0.01	0.03	0.12	0.31	0.40	0.52	0.68	0.93	0.89	0.58	0.41	0.33	0.22	0.07	0.02	0.01	0.00	5.52	0.00
-60	0.00	0.00	0.01	0.02	0.04	0.08	0.11	0.11	0.10	0.10	0.11	0.10	0.06	0.03	0.02	0.01	0.00	0.00	0.90	0.00
-70	0.00	0.00	0.00	0.00	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.00	0.00	0.00	0.00	0.12	0.00
-80	0.00	0.00	0.00	0.00	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.00	0.00	0.00	0.00	0.12	0.00
-90	0.00	0.00	0.00	0.00	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.00	0.00	0.00	0.00	0.12	0.00
-90 -80 -70 -60 -50 -40 -30 -20 HORIZONTAL (DEG) 20 30 40 50 60 70 80 90																				
Φ t	0.04	0.57	7.96	48.0	159	282	310	318	323	311	300	290	251	133	35.6	5.55	0.38	0.03	2776	---
Φ a	0.00	0.00	0.00	37.2	154	277	304	311	314	301	291	284	246	127	23.4	0.00	0.00	0.00	---	2670

one-half-peak spread: U:14.7,D:10.6 , L:16.4,R:15.4,Beam Type: Type 6 x 5 (H x V)

H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:28.9DEG
Operators:07
Test Date:2017-08-04

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.286
Humidity:54.0%
Test Distance:6.325m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:120.3V I:0.2117A P:25.31W PF:0.9936 Lamp Flux:2795.11x1 lm		
NAME: 投光灯具	TYPE:FLB	WEIGHT:
SPEC.:2002/1000WHQI	DIM.:	SERIAL No.:
MFR.: Above All Lighting	SUR.:	PROTECTION ANGLE:

Conical surface Flux(120deg):

2708.7 lm

%lum = 96.9%


%lamp = 96.9%

Conical surface Flux(120deg):

2708.7 lm

%lum = 96.9%

%lamp = 96.9%

H(β) Range:-90 - 90DEGH(β) Interval: 0.5DEG

Test Speed: HIGH

Temperature:28.9DEG

Operators:07

Test Date:2017-08-04

V(B) Range:-180 - 180DEG

V(B) Interval: 0.5DEG

Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.286


Humidity:54.0%

Test Distance:6.325m [K=1.0000]

Remarks:

ISOLUX DIAGRAM

Test:U:120.3V I:0.2117A P:25.31W PF:0.9936 Lamp Flux:2795.11x1 lm		
NAME: 投光灯具	TYPE:FLB	WEIGHT:
SPEC.:2002/1000WHQI	DIM.:	SERIAL No.:
MFR.: Above All Lighting	SUR.:	PROTECTION ANGLE:




H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:28.9DEG
Operators:07
Test Date:2017-08-04

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.286
Humidity:54.0%
Test Distance:6.325m [K=1.0000]
Remarks:

AAI Figure

Test:U:120.3V I:0.2117A P:25.31W PF:0.9936 Lamp Flux:2795.11x1 lm		
NAME: 投光灯具	TYPE:FLB	WEIGHT:
SPEC.:2002/1000WHQI	DIM.:	SERIAL No.:
MFR.: Above All Lighting	SUR.:	PROTECTION ANGLE:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:28.9DEG
Operators:07
Test Date:2017-08-04

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.286
Humidity:54.0%
Test Distance:6.325m [K=1.0000]
Remarks:

Planar Illuminance Curve



H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:28.9DEG
Operators:07
Test Date:2017-08-04

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.286
Humidity:54.0%
Test Distance:6.325m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:120.3V I:0.2117A P:25.31W PF:0.9936 Lamp Flux:2795.11x1 lm		
NAME: 投光灯具	TYPE:FLB	WEIGHT:
SPEC.:2002/1000WHQI	DIM.:	SERIAL No.:
MFR.: Above All Lighting	SUR.:	PROTECTION ANGLE:

Table--1

UNIT: cd

H (DEG) V (DEG)	-90	-85	-80	-75	-70	-65	-60	-55	-50	-45	-40	-35	-30	-25	-20	-15	-10	-5	0
-180	0.11	0.13	0.20	0.35	0.73	1.34	2.19	3.22	4.23	4.98	5.50	5.79	6.12	6.45	6.75	6.92	6.97	7.00	7.19
-170	0.11	0.14	0.22	0.42	0.87	1.57	2.51	3.56	4.55	5.33	5.72	5.85	5.89	5.94	6.01	6.12	6.24	6.43	6.61
-160	0.11	0.14	0.23	0.45	0.92	1.65	2.49	3.28	3.98	4.47	4.81	4.98	5.04	5.12	5.19	5.30	5.37	5.43	5.65
-150	0.11	0.14	0.23	0.44	0.87	1.35	1.93	2.55	3.09	3.53	3.85	4.12	4.28	4.43	4.53	4.57	4.57	4.57	4.79
-140	0.11	0.14	0.22	0.40	0.65	0.96	1.35	1.73	2.10	2.42	2.67	2.86	3.02	3.11	3.13	3.09	3.08	3.15	3.44
-130	0.11	0.14	0.21	0.30	0.44	0.62	0.82	1.01	1.19	1.34	1.47	1.57	1.61	1.59	1.57	1.51	1.51	1.62	1.82
-120	0.11	0.14	0.18	0.23	0.28	0.36	0.44	0.50	0.55	0.58	0.61	0.61	0.60	0.58	0.58	0.57	0.57	0.63	0.72
-110	0.11	0.13	0.17	0.18	0.18	0.20	0.22	0.23	0.22	0.22	0.23	0.24	0.24	0.27	0.30	0.32	0.34	0.37	0.39
-100	0.11	0.12	0.15	0.14	0.13	0.14	0.15	0.14	0.13	0.14	0.15	0.15	0.15	0.17	0.19	0.20	0.20	0.23	0.26
-90	0.11	0.12	0.13	0.13	0.12	0.12	0.13	0.12	0.12	0.12	0.12	0.12	0.11	0.12	0.12	0.12	0.12	0.13	0.15
-80	0.11	0.14	0.20	0.26	0.31	0.39	0.46	0.53	0.58	0.66	0.75	0.95	1.21	1.40	1.56	1.60	1.57	1.45	1.30
-70	0.11	0.22	0.40	0.61	0.85	1.15	1.56	2.10	2.82	3.81	4.98	6.10	6.83	6.95	6.58	6.29	6.12	5.94	5.65
-60	0.11	0.32	0.68	1.03	1.59	2.89	5.82	17.7	28.9	40.5	45.8	42.8	55.0	52.5	56.9	63.0	71.6	74.3	73.7
-50	0.11	0.45	0.97	1.57	3.67	8.40	32.0	74.6	133	258	485	669	774	800	826	840	852	817	738
-40	0.11	0.61	1.27	2.57	7.00	25.0	60.0	158	330	718	1127	1507	1687	1666	1564	1576	1589	1579	1535
-30	0.11	0.76	1.55	4.18	13.3	45.6	130	264	592	1046	1524	1897	1979	1871	1824	1826	1825	1834	1875
-20	0.11	0.88	1.80	5.54	22.9	64.4	177	327	683	980	1297	1486	1431	1364	1288	1233	1218	1207	1169
-10	0.11	0.98	1.99	6.12	31.3	88.0	173	365	675	850	1108	1189	1139	1113	1074	1036	1011	1000	999
0	0.11	1.04	2.09	6.21	34.5	97.9	151	410	728	822	1085	1223	1089	1087	1097	1077	1043	1021	1015
10	0.11	0.99	2.09	5.81	31.5	88.4	140	370	704	795	1044	1202	1077	1044	1029	1002	988	980	970
20	0.11	0.90	2.02	5.11	22.1	65.9	122	266	623	757	957	1157	1095	971	944	931	934	933	929
30	0.11	0.77	1.87	3.71	10.9	35.9	74.6	132	398	638	745	882	949	861	825	837	837	838	792
40	0.11	0.63	1.63	2.74	5.22	11.7	12.8	38.9	96.9	232	303	324	319	320	317	324	321	294	226
50	0.11	0.47	1.23	2.25	3.69	4.44	7.11	10.3	15.2	19.3	20.5	31.1	33.3	41.1	49.5	62.1	74.2	82.8	90.4
60	0.11	0.35	0.77	1.45	2.60	4.21	6.75	10.2	14.1	18.0	14.9	11.9	21.4	32.8	40.8	46.8	54.1	56.4	56.0
70	0.11	0.23	0.45	0.68	0.91	1.53	2.57	6.20	14.4	15.2	9.04	6.24	5.86	12.7	25.0	32.6	38.0	36.5	33.4
80	0.11	0.14	0.23	0.30	0.35	0.40	0.43	0.49	0.52	0.56	0.57	0.60	0.61	0.65	0.70	0.75	0.79	0.74	0.67
90	0.11	0.11	0.11	0.11	0.11	0.11	0.11	0.11	0.11	0.11	0.11	0.11	0.11	0.11	0.11	0.11	0.12	0.12	0.13
100	0.11	0.11	0.11	0.11	0.12	0.12	0.12	0.14	0.16	0.16	0.15	0.16	0.15	0.14	0.13	0.13	0.14	0.14	0.13
110	0.11	0.11	0.11	0.13	0.16	0.19	0.22	0.30	0.40	0.50	0.61	0.67	0.69	0.68	0.63	0.60	0.54	0.55	0.56
120	0.11	0.11	0.12	0.16	0.21	0.30	0.47	0.73	1.06	1.46	1.86	2.24	2.44	2.57	2.59	2.55	2.43	2.45	2.48
130	0.11	0.12	0.14	0.20	0.30	0.49	0.86	1.43	2.13	2.94	3.72	4.42	4.92	5.27	5.50	5.67	5.61	5.62	5.64
140	0.11	0.12	0.16	0.24	0.41	0.76	1.33	2.18	3.24	4.28	5.15	5.82	6.34	6.75	7.14	7.45	7.58	7.63	7.66
150	0.11	0.13	0.18	0.28	0.53	1.02	1.77	2.79	3.99	5.11	5.92	6.42	6.70	6.96	7.22	7.44	7.62	7.76	7.74
160	0.11	0.13	0.19	0.32	0.65	1.21	2.05	3.18	4.39	5.44	6.21	6.73	7.10	7.46	7.87	8.26	8.41	8.38	8.17
170	0.11	0.13	0.20	0.35	0.72	1.34	2.22	3.31	4.43	5.34	6.02	6.46	6.86	7.24	7.52	7.72	7.85	8.04	8.12
180	0.11	0.13	0.20	0.35	0.73	1.34	2.19	3.22	4.23	4.98	5.50	5.79	6.12	6.45	6.75	6.92	6.97	7.00	7.19

H(β) Range:-90 - 90DEG

H(β) Interval: 0.5DEG

Test Speed: HIGH

Temperature:28.9DEG

Operators:07

Test Date:2017-08-04

V(B) Range:-180 - 180DEG

V(B) Interval: 0.5DEG

Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.286

Humidity:54.0%

Test Distance:6.325m [K=1.0000]

Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:120.3V I:0.2117A P:25.31W PF:0.9936 Lamp Flux:2795.11x1 lm		
NAME: 投光灯具	TYPE:FLB	WEIGHT:
SPEC.:2002/1000WHQI	DIM.:	SERIAL No.:
MFR.: Above All Lighting	SUR.:	PROTECTION ANGLE:

Table--2

UNIT: cd

H (DEG) V (DEG)	5	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	
-180	6.89	6.75	6.66	6.60	6.45	6.43	6.49	6.49	6.16	5.53	4.59	3.45	2.36	1.49	0.83	0.42	0.24	0.17	
-170	6.42	6.33	6.32	6.32	6.20	6.09	6.05	5.92	5.56	5.02	4.20	3.19	2.21	1.41	0.80	0.41	0.24	0.17	
-160	5.64	5.65	5.69	5.72	5.66	5.54	5.44	5.22	4.86	4.35	3.63	2.76	1.93	1.25	0.73	0.38	0.23	0.17	
-150	4.85	4.84	4.87	4.86	4.79	4.70	4.55	4.28	3.97	3.54	2.95	2.23	1.58	1.04	0.62	0.35	0.23	0.17	
-140	3.58	3.60	3.59	3.59	3.56	3.50	3.40	3.22	2.95	2.57	2.12	1.65	1.19	0.80	0.50	0.31	0.22	0.17	
-130	1.95	2.02	2.00	2.05	2.07	2.07	2.05	1.98	1.81	1.59	1.33	1.07	0.82	0.57	0.38	0.27	0.21	0.17	
-120	0.77	0.80	0.80	0.82	0.84	0.88	0.89	0.90	0.87	0.80	0.72	0.61	0.50	0.38	0.29	0.23	0.20	0.17	
-110	0.39	0.38	0.36	0.35	0.33	0.32	0.32	0.33	0.34	0.33	0.33	0.31	0.28	0.24	0.22	0.21	0.18	0.17	
-100	0.25	0.24	0.24	0.23	0.21	0.19	0.19	0.19	0.17	0.16	0.17	0.18	0.18	0.17	0.18	0.18	0.18	0.17	
-90	0.15	0.14	0.15	0.15	0.14	0.14	0.14	0.14	0.14	0.14	0.14	0.15	0.15	0.15	0.16	0.17	0.17	0.17	
-80	1.38	1.41	1.30	1.18	1.01	0.86	0.76	0.68	0.66	0.61	0.55	0.47	0.41	0.34	0.27	0.21	0.17	0.17	
-70	5.62	5.59	6.00	6.40	6.66	6.51	5.27	3.68	2.78	2.27	1.75	1.37	1.11	0.87	0.64	0.42	0.23	0.17	
-60	70.4	63.2	50.1	41.5	39.8	36.1	30.1	35.7	28.8	19.0	7.60	3.48	2.10	1.53	1.05	0.68	0.31	0.17	
-50	686	658	660	659	636	618	505	315	153	89.0	46.8	17.2	5.02	2.69	1.63	0.97	0.40	0.17	
-40	1508	1512	1529	1557	1660	1592	1321	896	495	190	95.7	30.9	14.6	5.37	2.29	1.24	0.51	0.17	
-30	1882	1869	1867	1879	1967	2132	1872	1336	868	414	160	87.7	38.7	10.5	3.13	1.51	0.62	0.17	
-20	1160	1167	1187	1246	1323	1350	1419	1164	853	571	226	136	64.4	17.1	4.11	1.71	0.71	0.17	
-10	1007	1021	1048	1090	1115	1134	1199	1058	804	641	290	137	74.9	23.1	4.63	1.84	0.77	0.17	
0	1024	1050	1085	1095	1079	1060	1174	1059	817	665	308	129	73.1	23.8	4.63	1.88	0.80	0.17	
10	964	963	962	981	1029	1067	1122	1039	821	632	289	119	47.0	15.2	3.98	1.76	0.76	0.17	
20	927	924	917	914	928	997	1034	905	749	504	186	92.9	17.2	7.10	3.13	1.57	0.69	0.17	
30	653	634	635	617	592	556	528	467	369	202	58.3	26.7	7.40	3.81	2.35	1.32	0.60	0.17	
40	149	117	114	93.6	90.7	79.6	64.2	65.3	53.0	28.8	17.6	8.12	5.68	3.55	1.79	1.06	0.49	0.17	
50	89.4	82.3	69.3	56.6	47.4	33.8	22.2	21.2	21.8	20.1	17.2	10.7	4.99	2.77	1.22	0.81	0.39	0.17	
60	56.1	55.7	51.9	42.8	27.1	15.6	10.8	13.6	18.3	18.3	14.2	5.89	2.76	1.19	0.80	0.57	0.30	0.17	
70	23.2	13.5	11.1	8.18	4.41	3.10	3.36	4.07	4.00	2.28	1.46	1.09	0.84	0.70	0.54	0.38	0.22	0.17	
80	0.76	0.83	0.82	0.79	0.75	0.71	0.66	0.62	0.60	0.56	0.52	0.47	0.42	0.35	0.28	0.20	0.15	0.17	
90	0.12	0.12	0.11	0.11	0.11	0.10	0.10	0.10	0.10	0.11	0.11	0.11	0.11	0.11	0.11	0.11	0.14	0.17	
100	0.14	0.15	0.14	0.13	0.14	0.15	0.16	0.17	0.18	0.18	0.16	0.15	0.14	0.13	0.12	0.11	0.14	0.17	
110	0.63	0.68	0.71	0.72	0.76	0.78	0.78	0.74	0.65	0.55	0.42	0.31	0.24	0.19	0.14	0.12	0.15	0.17	
120	2.64	2.74	2.76	2.75	2.72	2.63	2.48	2.18	1.84	1.42	1.04	0.69	0.43	0.28	0.19	0.14	0.16	0.17	
130	5.77	5.82	5.76	5.62	5.40	5.11	4.72	4.16	3.48	2.71	1.93	1.23	0.73	0.41	0.25	0.18	0.17	0.17	
140	7.76	7.83	7.80	7.63	7.21	6.76	6.25	5.66	4.89	3.92	2.81	1.82	1.06	0.57	0.31	0.23	0.18	0.17	
150	7.87	8.01	8.10	7.94	7.60	7.15	6.81	6.35	5.67	4.67	3.48	2.30	1.36	0.72	0.44	0.28	0.20	0.17	
160	7.94	7.94	8.02	7.89	7.49	7.04	6.80	6.52	5.94	5.00	3.79	2.55	1.61	1.00	0.59	0.33	0.22	0.17	
170	7.84	7.72	7.71	7.60	7.22	6.83	6.55	6.29	5.78	5.10	4.13	3.04	2.05	1.28	0.73	0.38	0.23	0.17	
180	6.89	6.75	6.66	6.60	6.45	6.43	6.49	6.49	6.16	5.53	4.59	3.45	2.36	1.49	0.83	0.42	0.24	0.17	

H(β) Range:-90 - 90DEGH(β) Interval: 0.5DEG

Test Speed: HIGH

Temperature:28.9DEG

Operators:07

Test Date:2017-08-04

V(B) Range:-180 - 180DEG

V(B) Interval: 0.5DEG

Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.286

Humidity:54.0%

Test Distance:6.325m [K=1.0000]

Remarks: