# CA commercial architecture

## **Historic Buildings**

Iconic Chicago Tower
PTACs And IAQ





### Scene-control solution

Ratio is said to be an easy-to-use, easy-to-install architectural solution for scene control and has three components: a Flat sensor, small power supply, and matchbook-size pushbutton controller. The device controls as many as 35 LED fixtures. Scenes use Bluetooth programming.

B.E.G. Controls, Peachtree City, GA

Circle 71 begcontrols.com

### LED area light

The LED small MT area light has applications in site, area, parking, walkways, and general lighting. The fixture is available in 40, 60, and 80 W for replacements to 200-W high-pressure sodium fixtures. The lightweight luminaire can be customized with several mounting options and has a tempered-glass lens.

Above All Lighting, Toms River, NJ

Circle 72

abovealllighting.com





### Trimless, flush-mount additions

Additions to the lolite series of modular LED downlights include trimless and flush-mount models. The trimless version has no exposed flange and does not extend below the ceiling plane. The flush mount has a visible round- or square-trim flange. Color temperatures for each range from 2700 to 5000 K.

Nora Lighting, Commerce, CA

Circle 73 noralighting.com



# Water-proof, pressure-proof luminaire

Tri-Proof lights are water-, pressure-, and dust-proof luminaires that replace traditional linear fluorescents. Rugged and resistant to heavy impacts, applications include factories, warehouses, and parking garages. A range of color temperatures is available.

National Specialty Lighting, Tonawanda, NY

Circle 74 nslusa.com

### Pop-up power dock

The PCS64 press-to-pop-up power dock provides three power outlets. The tower has an LED-

powered trim ring, making it easy to spot when closed. Installation in reportedly any type of furniture is through a 3 3/4-in. hole, dropped in from the top and tightened underneath with a locking ring.

Doug Mockett & Co., Manhattan Beach, CA

Circle 75 mockett.com



### Compact high bay

The HP series LED high-bay pendant provides high output illuminations for large-scale interiors. Available in a full range of wattages, the luminaire provides 28,500 lumens with reported minimal glare and measures less than 14 in. in diameter. It is a direct replacement for 175- to 600-W metal-halide or HID fixtures. MaxLite, West Caldwell, NJ

Circle 76 maxlite.com

