

# 2.3" MAGIC DIRECT LED LINEAR LIGHT

## Recessed / Suspended / Surface Mounted



### PRODUCT DESCRIPTION

The 2.3" Magic Linear Light is available in recessed mount. It is available in 2.3" width with 2ft, 3ft, 4ft and 8ft lengths options, simply provide linear, powerful lighting to any atmosphere. This linear lighting features a streamlined linear form factor designed for maximum versatility. With their superior flexibility by wattage selectable and CCT adjustable, Magic Linear creates a balance between esthetics, visual comfort and lighting performance, designed to meet the most demanding lighting challenges.


### FEATURES

- Trimless recessed, suspended and surface mounted
- T-grid or dry ceiling compatible
- Continuous runs or custom pattern
- Available in 2ft, 3ft, 4ft and 8ft
- Wattage selectable (50%/75%/100%)
- 3000K, 3500K, 4000K selectable

### ELECTRICAL SYSTEM

- Input Voltage: 120-277V, 50/60Hz
- Operating temperature range: -4-104°F (-20-40°C)
- Power Factor: > 0.9 at full load
- Total Harmonic Distortion: < 20% at full load

### SPECIFICATION



### PERFORMANCE

CRI

80

CCT

3000K, 3500K, 4000K

Dimming

1-10V Dimming

Compatible Dimmer

LUTRON: DVSTV

LEVITON: IP710

Projected Lifetime

L70 - 100,000 Hours



Working Temperature

-4-104°F (-20-40°C)



Certifications

- cULus conforms to UL Std. 1598Cert. to CSA Std. C22.2 No.250.0
- Suitable for damp locations
- RoHS compliant

## RECESSED IN DRY CEILING




## RECESSED IN GRID CEILING



## Ordering Information

### Example: MAG1223-SW1-RM-D-FDL



#### 1. Series

MAG

#### 2. Length

06 - 2FT     09 - 3FT     12 - 4FT     24 - 8FT

**Option** - Desired System Length\*

\* Individual fixtures, Runs and Configurations are supplied in nominal lengths to ensure full, even, illumination. If desired runs and configurations are needed, please tell us the details in advance. Then we can prepare the middle run and end run in factory for easy installation, or end user need to modify the standard individual fixtures into middle run and end run.

#### 3. Width

23- 2.3 Inch

#### 4. Driver

Blank - Integral

#### 5. CCT

SW- 3000K/3500K/4000K Selectable

1. Default setting is 3500K.

#### 6. Voltage

1 - 120-277V

#### 7. Mounting Options

RSM - Recessed / Suspended / Surface Mounted

\* Please refer to the following accessory table to choose the right mounting kits.

#### 8. Light Distribution

D - 100% Downlight

#### 9. Lens Options

FDL - Flush Diffused Lens     RGL - Regressed Lens

\* FDL is standard. RGL will ask MOQ and long lead time.

\* Continuous run mount is not available for regressed lens.

\* If the joined length exceeds 8ft, only continuous Roll-Out Lens can be used.

#### 10. Finish

Blank - White

BK - Black

## Accessories (ordered separately and field installed)

### For Recessed Mount



#### MAG0623-RMK1

Recessed Mount Kit for  
2ft, 2.3" Linear  
Dry Ceiling Mount  
(One set per fixture)

#### MAG0923-RMK1

Recessed Mount Kit for  
3ft, 2.3" Linear  
Dry Ceiling Mount  
(One set per fixture)

#### MAG1223-RMK1

Recessed Mount Kit for  
4ft, 2.3" Linear  
Dry Ceiling Mount  
(One set per fixture)



#### MAG23-RMK2

Recessed Mount Kit for  
Drop Ceiling (One set  
per fixture)

\* If for 8ft, 2.3" Linear, two sets of **MAG1223-RMK1** will be needed.

### For Suspended Mount

#### Drop Ceiling Suspension Mount List



#### MAG-PMK3-5FT

Aircraft Cable Pendant  
Mount Kits for Drop Ceiling,  
with 5ft aircraft cable  
and 5ft power cord  
( One set per fixture)

#### MAG-PMK3-12FT

Aircraft Cable Pendant  
Mount Kits for Drop Ceiling,  
with 12ft aircraft cable  
and 12ft power cord  
( One set per fixture)

\* Suitable for 9/16" and 15/16" Flat Ceiling.  
If for 9/16" slot ceiling please contact Customer Service.

### For Suspended Mount

#### Dry Ceiling Suspension Mount List




#### MAG-PMK1-5FT

Aircraft Cable Pendant  
Mount Kits for Dry Ceiling,  
with 5ft aircraft cable  
and 5ft power cord  
( One set per fixture)

#### MAG-PMK1-12FT


Aircraft Cable Pendant  
Mount Kits for Dry Ceiling,  
with 12ft aircraft cable  
and 12ft power cord  
( One set per fixture)

### For Surface Mount




#### MAG-SMK

Surface and Wall Mount Kits



**MAG23-RSM-L**

L Shape Mount Bracket  
for Recessed, Suspended  
and Surface Mount




**MAG23-RSM-LINE**

Line Shape Mount Bracket  
for Recessed, Suspended  
and Surface Mount



**MAG23-ROL<sup>1</sup>**

Continuous Roll-Out  
Lens (42')



**EBU-H08170<sup>2</sup>**

8W Emergency Battery  
Back-up for MAX.60W fixture



**AAL-RC-100**

Remote Control for  
Microwave Motion Sensor



**MAG-MSW-PM/SM**

Microwave Motion Sensor Kits  
for pendant mount

**EBU-H25170<sup>2</sup>**

25W Emergency Battery  
Back-up for MAX.200W fixture


**Notes:**

1. If the joined length exceeds 8ft, only continuous Roll-Out Lens can be used.
2. Emergency battery back-up is for ambient temperatures of 32°F -95°F (0 °C -35°C).

## PHOTOMETRY


All published luminaire photo metric testing performed to IESNA LM-79-08 standards by a NVLAP certified laboratory. IESNA LM-79-08 specifies the entire luminaire as the source resulting in a fixture efficiency of 100%. Result may vary per actual order.

### With Flush Diffused Lens



AVERAGE BEAM ANGLE(50%): 111.3°

### With Regressed Lens




AVERAGE BEAM ANGLE(50%): 92.7°

## PERFORMANCE DATA


Lumen values are measured by third party certified laboratories performed in accordance with IESNA LM-79-08 as well as Lighting Facts listed.

Ref#: 20240510

Flush Diffused Lens



Regressed lens



Lens	Lumen Package		
	High	Medium	Low
Flat lens	1000lm/ft, 10W/ft	750lm/ft, 7.5W/ft	500lm/ft, 5W/ft
Regressed	800lm/ft, 10W/ft	600lm/ft, 7.5W/ft	400lm/ft, 5W/ft
Width	2.3"	2.3"	2.3"
Wattage	10W/15W/20W@2FT 15W/20W/30W@3FT 20W/30W/40W@4FT 40W/60W/80W@8FT		

**Notes:**

Above are subject to 3500K.

All efficacy is  $\pm 5\%$  base on different CCT and wattage. Check the IES file to gain the accurate data .

## Warranty

Five year limited warranty.