

Optional Pole Finishing



Light wood texture

Deep wood texture





ABOVE ALL www.AboveAllLighting.com

TECHNICAL DATA

Wattage	10W
CRI	80
ССТ	3000K, 4000K
Dimming	Non-Dimming
Input Voltage	120-277V, 50/60Hz
Operating Temp.	-22°F to 104°F(-30°C to 40°C)
Certifications	cETL listed
	Suitable for wet location
	RoHS compliant
Power Factor	>0.9 at 120 Vac
Harmonic Distortion	<20% at full load
Projected Lifetime	L70 - 100,000 Hours
IP Rating	IP65

FEATURES

- Optimized Visual Comfort: Fully shielded light source.
- Versatile Application: Ideal for a wide range of exterior spaces.
- Premium Construction: UV powder-coated die-cast aluminum body. Molded silicone gasket & stainless steel screws.

ARBOR LED BOLLARD



SPECIFICATION

Dimension



ORDERING INFORMATION

EXAMPLE: ARBD32H-10401-BK

ARBD Series	Height	Wattage	ССТ	Voltage	Control	Finish
ARBD Arbor Bollard	32H 31.5" Height	10 10W	30 3000К 40 4000К	1 120-277V	BLANK On/Off	BK Black Wood Texture Optional ¹ Additional fees applied.

NOTE:

1. The standard color is black finish; Wood texture finish and other optional finish colors are available at an additional charge. Please contact Customer Service for details.

ARBOR LED BOLLARD



Ref#: 20250521

WOOD TEXTURE OPTIONS



LWTC-1/2-TP

Pole finish 1/2 light wood texture on the top, and 1/2 black on the bottom. **LWTC-2/3-TP** Pole finish 2/3 light wood texture on the top, and 1/3 black on the bottom.



DWTC-1/2-TP Pole finish 1/2 deep wood texture on the top, and 1/2 black on the bottom. DWTC-2/3-TP Pole finish 2/3 deep wood texture on the top, and 1/3 black on the bottom.

Notes: For alternative finish/paint ratios, please contact Customer Service.

ACCESSORIES (ORDERED SEPARATELY)



ABMK-ARBD

Anchor Bolts Mounting Kits.

PERFORMANCE DATA

Lumen values are measured by third party certified laboratories performed in accordance with IESNA LM-79-08 as well as Lighting Facts listed.

Wattage	Lumen Output	AC Input 120V	CRI	ССТ
10W	490LM	0.08A	80	3000K

BUG RATING TABLE

Performed to IESNA LM-79-08 standards by a NVLAP accredited laboratory.

Model	BUG Rating
ARBD32H_10301_BK	B0-U2-G0
ARBDXXH_10301_BK	B0-U2-G0

WARRANTY

5 years limited warranty. Specifications subject to change without notice.