

PILLAR ROUND POLE LIGHT



PRODUCT DESCRIPTION

The Pillar round led pole light is well constructed with high quality extruded aluminum, UV powder coated, featuring tempered safety glass, moulded silicone gasket and stainless steel screws. This impressive pole light is an excellent choice for walkways, entrances, promenades, plazas, courtyards, driveways, bridges, and landscaped areas.

ELECTRICAL SYSTEM

- Input Voltage: 120-277VAC, 50/60Hz
- Operating temperature range: -40-104°F (-40-40°C)
- Power Factor: > 0.9
- Total Harmonic Distortion: < 20% at full load

PERFORMANCE

CRI

80

CCT

2700K, 3000K, 4000K

Dimming

0-10V dimming

Projected Lifetime

L70 - 100,000 Hours


Working Temperature

-40-104°F (-40-40°C)


Certifications

- cETL Listed
- IP65 rated
- RoHS compliant

SPECIFICATION



Pole Base



Ordering Information

Example: PRPL-4FT-4530801-BK

Name	Pillar Height¹	Watts	CCT	CRI	Voltage	- Control	- Finish
PRPL	4FT - 4.1 feet	25 - 25W	27- 2700K	80- CRI80	1-120-277V	Blank - None	BK - Black
		45 - 45W	30- 3000K				
			40- 4000K				

Notice:

1. Pillar and pole height can be customized. Pole need to be ordered separately. Please check with Customer Service for details.
- * Standard Finish is Black. Custom colors might be available at an additional charge.

ACCESSORIES (ORDER SEPARATELY)



ABMK-PRPL-6T13FT

Anchor bolts mounting kits
for 6ft to 13ft pillar round pole light

ABMK-PRPL-15T18FT

Anchor bolts mounting kits
for 15ft to 18ft pillar round pole light



PRPL-2.5FT-POLE-BK

2.46 feet pole, black

* Pole height and finish color can be customized.

PERFORMANCE DATA

LUMEN OUTPUT

Lumen values are measured by third party certified laboratories performed in accordance with IESNA LM-79-08 as well as Lighting Facts listed.

Nominal Watts	Lumen Output	CCT	CRI
25W	1800lm	4000K	80
45W	3800lm	4000K	80

Warranty

Five year limited warranty.

Specifications subject to change without notice.