VERTICAL MINI LED STEP LIGHT











3W LED Step/Wall Lights are available in a vertical configuration for mounting into a junction box. For poured concrete and masonry installations. For indoor and protected outdoor use.


TECHNICAL DATA


Wattage	3W	
ССТ	3000K	
Dimming	Non-Dimming	
CRI	80	
Input Voltage	120V, 50/60Hz	
Projected Lifetime	L70-100,000 Hours	
Operating Temp.	-13°F to 95°F (-25°C to 35°C)	
Certifications	ETL listed	
	Suitable for wet locations	
	RoHS compliant	
Power Factor	>0.87	



SPECIFICATION

Dimension





ORDERING INFORMATION

EXAMPLE:VMSL03304-BK

Model	Wattage	ССТ	Voltage	Controls	Finish
VMSL	03	30	4	BLANK	BK¹
	3W	3000K	120V	On/Off	Black¹

NOTE:

- 1. Black finish is standard. Custom finish colors are available at an additional charge. Please contact Customer Service for premium options.
- 2. Minimum order required, please contact Customer Service for additional information.

PERFORMANCE DATA


Lumen values are measured by third party certified laboratories performed in accordance with IESNA LM-79-08 as well as Lighting Facts listed.

Wattage	Lumen Output	AC Input 120V	ССТ	CRI
3W	80lm	0.03A	3000K	80



PHOTOMETRY

All published luminaire photometric testing performed to IESNA LM-79-08 standards by a NVLAP certified laboratory. IESNA LM-79-08 specifies the entire luminaire as the source resulting in a fixture efficiency of 100%. Result may vary per actual order.



BUG RATING TABLE

Performed to IESNA LM-79-08 standards by a NVLAP accredited laboratory.

Model	BUG Rating
VMSL03304-BK	B0-U1-G0

WARRANTY

2 year limited warranty.

Specifications subject to change without notice.