



The MACK LED Bollard comes in simple and modern rectangular design. Fully shielded design used to control unwanted light in residential areas. This bollard has UV powder coated die cast high quality aluminum body, tempered safety glass, moulded silicone gasket and stainless steel screws. This bollard is an excellent choice for walkways, entrances, promenades, plazas, courtyards, driveways, bridges, and landscaped areas.

TECHNICAL DATA

Wattage	10W
CCT	3000K, 4000K
	3000K-DarkSky Approved
Dimming	Non-Dimming is standard
	0-10V Dimming is optional
CRI	80
Input Voltage	120-277V, 50/60Hz
Projected Lifetime	L70-100,000 Hours
Operating Temp.	-30°C to 40°C (-86°F to 104°F)
Certifications	cETLus
	RoHS compliant
	DarkSky Approved for CCT of
	3000K and below
Power Factor	>0.9 @120Vac
Harmonic Distortion	<20% at full load
IP Rating	IP65


FEATURES

- Fully shielded design.
- Die cast aluminum body.
- Tempered safety glass.
- IP65 rated for wet location.


SPECIFICATION

Dimension


Side View



Base Plate



Anchor Bolt



ORDERING INFORMATION

Standard Model

EXAMPLE: MBD24H-STB-10401-V-BK

MBD								
Series	Height	Base	Wattage	CCT	Voltage	Distribution	Finish	Options
MBD Mack Bollard	24H 23.6" Height	STB	10 10W	30 3000K 40 4000K	1 120-277V	V Type V	BK Black Optionaal Finish Colors (Additional Charge applied) ¹	BLANK Non- Dimming D 0-10V Dimming Driver

NOTE:

1. Black finish is standard. Additional charges will apply for all the other colors. Please contact Customer Service for premium options.

ORDERING INFORMATION

DarkSky-Approved Model


EXAMPLE: MBD24H-STB-10301-V-BK-D

MBD								
Series	Height	Base	Wattage	CCT	Voltage	Distribution	Finish	Options
MBD Mack Bollard	24H 23.6" Height	STB	10 10W	30 3000K	1 120-277V	V Type V	BK Black Optionoal Finish Colors (Additional Charge applied) ¹	D 0-10V Dimming Driver

NOTE:

1. Black finish is standard. Additional charges will apply for all the other colors. Please contact Customer Service for premium options.

ACCESSORIES (ORDERED SEPARATELY)



91310
ABMK-MBD-SB
 Anchor Bolts Mounting Kits

PERFORMANCE DATA

Lumen values are measured by third party certified laboratories performed in accordance with IESNA LM-79-08 as well as Lighting Facts listed.

Wattage	Lumen Output	AC Input 120V	CRI	CCT	LPW
10W	700lm	0.08A	80	3000K	70

WARRANTY

5 year limited warranty.

Specifications subject to change without notice.