





### SURFACE MOUNT CLOSET LIGHT










### PRODUCT DESCRIPTION


The LED surface mount closet light comes with PIR motion sensor. It will turn ON automatically when motion is detected not only in the dark but also in the daylight and turn OFF after one minute when no motion is detected. Flush mount to a 4" junction box. It is ideal for closets, workrooms, basements, storage areas and attics etc.

#### **FEATURE**

- Input Voltage:120V
- Minimum Ambient -20°C, Maximum Ambient is 40°C
- Power Factor: > 0.9 at full load
- Total Harmonic Distortion: < 20% at full load

### **SPECIFICATION**





#### **PERFORMANCE**

CRI

90

CCT

2700K, 3000K, 3500K, 4000K, 5000K

**Dimming** 

Non-dimmable

**Projected Lifetime** 

L70 - 50,000 Hours

Working Temperature

-4-104°F (-20-40°C)

Certifications

- ETL Listed
- · Suitable for wet locations
- RoHs compliant



# **Ordering Information**

Example: CST07R-15-SW904-MS-WH

Name	Size	Shape	_ Watts	_CCT	CRI <sup>3</sup>	Voltage	_Controls	_ Finish
CST	<b>07</b> - 7.32"	<b>R</b> - Round	<b>15</b> - 15W	<b>SW</b> - 2700K 3000K 3500K 4000K 5000K Selectable <sup>1</sup>	<b>90</b> - 90CRI <sup>2</sup>	<b>4</b> - 120V	MS - PIR Motion Sensor <sup>2</sup>	<b>WH</b> - White

#### Notice:

- 1. 4000K is default setting.
- 2. The light will turn ON automatically when motion is detected not only in the dark but also in the daylight and turn OFF after one minute when no motion is detected.
- \* White finish is standard. Custom color is available at an additional charge. Consult customer service for details.

#### Accessories



SCB SPRING CARD BUCKLE



**E26LH**E26 LAMP HOLDER

#### PERFORMANCE DATA

Lumen values are measured by third party certified laboratories performed in accordance with IESNA LM-79-08 as well as Lighting Facts listed.


Watts	Lumen Output	Size	AC Input 120V	CCT	CRI	LPW
15	1130	7IN	0.12A	4000K	90	75



## **DETECTION RANGE**


#### **Wall Mount**

The mounting height is 6 feet. Sensing distance is 10 feet. Sensing range is 90 degrees.




#### **Ceiling Mount**

The mounting height is 11 feet. Sensing distance is 10 feet. Sensing range is 48 degrees.



## **PHOTOMETRY**



## Warranty

Five year limited warrant