



The Wet Magic LED Linear Light is a sleek 1.97"-wide luminaire for indoor/outdoor use in bathrooms, spas, garages, and canopies. Combining durability, flexibility, and high performance, it enables seamless runs (4'/6'/8') and offers suspended, recessed, surface, or wall mounting. Ideal for demanding projects requiring weatherproof, architectural-grade lighting with continuous illumination.

TECHNICAL DATA

Wattage	31W, 46W, 61W
Length	4ft, 6ft, 8ft
CRI	80
CCT	3000K, 3500K, 4000K
Integrated Driver	0-10V Dimming
Input Voltage	120-277V, 50/60Hz
Operating Temp.	-4°F to 104°F (-20°C to 40°C)
Certifications	ETL listed Suitable for wet locations RoHS compliant
Power Factor	>0.9 at full load
Harmonic Distortion	<20% at full load
Projected Lifetime	L70 - 100,000 Hours
IP Rating	65


Recessed



Surface Mounting



Wall Mounting



Suspended





FEATURES

- **Adjustable & Customizable:** Multiple lengths (4'/6'/8') with seamless continuous runs.
- **Robust Design:** IP65-rated for wet locations, with a 5-year warranty.
- **Versatile Project Adaptability:** 4 mounting configurations: suspended, recessed, surface, and wall mounting.


SPECIFICATION

Dimension

Cable length: 6 feet



Continuous Run



The Continuous Run Mounting Kit shall be specified from the accessory table when continuous illumination is required. Wet Linear is made up of standard 4' , 6' and 8' sections that can be joined cleanly and securely for continuous runs in all configurations onsite.

Luminaire Run Length	Run Configuration	Continuous Run Mounting Kit	Aircraft Cable
4'	4'	-	2
6'	6'	-	2
8'	8'	-	2
10'	6'+4'	1	3
12'	8'+4'	1	3
14'	8'+6'	1	3
16'	8'+8'	1	3
18'	6'+6'+6'	2	4
20'	8'+8'+4'	2	4
22'	8'+8'+6'	2	4
24'	8'+8'+8'	2	4
26'	8'+6'+6'+6'	3	5
28'	8'+8'+6'+6'	3	5
30'	8'+8'+8'+6'	3	5

ORDERING INFORMATION

EXAMPLE: WMAG1220-3135801-D-FDL-WH

WMAG					
1. Series	2. Length	3. Width	4. Wattage	5. CCT	6. CRI
WMAG Wet Magic	12 4ft	20 1.97 inch	31 31W(4ft)	30 3000K	80 80CRI
	20 6ft		46 46W(6ft)	35 3500K	
	24 8ft		61 61W(8ft)	40 4000K	
	7. Voltage	8. Light Distribution	9. Lens Options	10. Finish	
	1 120-277V	D 100% Downlight	FDL Flush Diffused Lens	WH White RAL9003 BK Black RAL9004 SL Silver RAL9006	


NOTE:

- Please specify mounting kits from the accessory table below for suspended, recessed, surface, or wall mounting.


Wall Mounting




Suspended



Recessed



Surface Mounting



Please specify mounting kits from the accessory table below.

ACCESSORIES (ORDERED SEPARATELY AND FIELD INSTALLED)



WMAG-PMK-WH

WMAG-PMK-BK

Aircraft Cable Suspension Mounting Kit for dry ceiling. White/Black. Includes 2 canopies, 2 aircraft cables, and 2 brackets for 1 fixture.



WMAG-SMK

Mounting Kit for surface mounting. Includes 2 brackets for 1 fixture.



WMAG-RPMK-0306-WH

WMAG-RPMK-0306-BK

Rod Pendant Mounting Kit. 11.8"-23.6" (30-60cm) adjustable. White/Black. Includes 2 rods, 2 canopies and 2 brackets for 1 fixture.



WMAG-WMK

Mounting Kit for wall mounting. Includes 2 brackets for 1 fixture.



WMAG-RMK

Recessed Mounting Kit. Includes 2 brackets for 1 fixture.



WMAG-CABLE-4FT-5PIN

4ft, 5-Pin Connection Cable with a waterproof connector. Current $\leq 6A$.



WPFCNT-5PIN

5-Pin Waterproof Connector.




WMAG-CRMK

Continuous Run Mounting Kit.

PHOTOMETRY

All published luminaire photometric testing performed to IESNA LM-79-08 standards by a NVLAP certified laboratory. IESNA LM-79-08 specifies the entire luminaire as the source resulting in a fixture efficiency of 100%. Results may vary per actual order.



PERFORMANCE DATA

Lumen values are measured by third party certified laboratories performed in accordance with IESNA LM-79-08 as well as Lighting Facts listed.

Length	Width	Wattage	Lumen @3500K	Voltage	Installation
4ft	1.97"	31W	3000lm	120-277V (Int.Driver)	Suspended / Recessed / Wall / Surface Mounting
6ft	1.97"	46W	4300lm	120-277V (Int.Driver)	Suspended / Recessed / Wall / Surface Mounting
8ft	1.97"	61W	5700lm	120-277V (Int.Driver)	Suspended / Recessed / Wall / Surface Mounting

WARRANTY

5 years limited warranty.
Specifications subject to change without notice.