



The Deep Focus Round Light offers the Focus family more choices. Fixture comes in diameters from 11.8" through 23.6". Deep recessed light source design achieving perfect glare control. Flexible installations come in pendant and surface mounted. Direct and indirect lighting for option. The Deep Focus Light is perfect for both commercial and residential applications.

TECHNICAL DATA

Wattage	
Direct	15W, 20W, 25W, 40W
Direct and Indirect	50W, 80W
CCT	3000K, 3500K, 4000K
Driver	0-10V Dimming standard
CRI	90Ra
Input Voltage	120-277V, 50/60Hz
Projected Lifetime	L70-100,000 Hours
Operating Temp.	-4°F to 104°F (-20°C to 40°C)
Certifications	cETLus conforms to UL Std. 1598
	Cert. to CSA Std. C22.2 No.250.0
	RoHS compliant
	Suitable for damp locations
Power Factor	>0.9 at full load
Harmonic Distortion	<20% at full load

FEATURES

- Fixtures in diameters from 11.8" through 23.6".
- Deep recessed light source design.
- Pendant or surface mounted.
- Direct and indirect lighting for option.









SPECIFICATION

Dimension

Aircraft Cable and Wire Cord Length: 59" (1500mm).

Pendant Rod Length: 47.2" (1200mm).

Suspended - Down 	Dimension				
	Model No.	D	H	A	B
	15W	11.8"(D300mm)	4.0"(100mm)	10.0"(250mm)	1.38"(35mm)
	20W	15.7"(D400mm)	4.0"(100mm)	10.0"(250mm)	1.38"(35mm)
	25W	18.9"(D480mm)	4.0"(100mm)	10.0"(250mm)	1.38"(35mm)
	40W	23.6"(D600mm)	4.0"(100mm)	10.0"(250mm)	1.38"(35mm)
Suspended - Up and Down 	Dimension				
	Model No.	D	H	A	B
	50W	18.9"(D480mm)	4.0"(100mm)	10.0"(250mm)	1.38"(35mm)
	80W	23.6"(D600mm)	4.0"(100mm)	10.0"(250mm)	1.38"(35mm)
Stem - Down 	Dimension				
	Model No.	D	H	A	B
	15W	11.8"(D300mm)	4.0"(100mm)	5.0"(127mm)	1.4"(36mm)
	20W	15.7"(D400mm)	4.0"(100mm)	5.0"(127mm)	1.4"(36mm)
	25W	18.9"(D480mm)	4.0"(100mm)	5.0"(127mm)	1.4"(36mm)
	40W	23.6"(D600mm)	4.0"(100mm)	5.0"(127mm)	1.4"(36mm)
Stem - Up and Down 	Dimension				
	Model No.	D	H	A	B
	50W	18.9"(D480mm)	4.0"(100mm)	5.0"(127mm)	1.4"(36mm)
	80W	23.6"(D600mm)	4.0"(100mm)	5.0"(127mm)	1.4"(36mm)

Surface Mounted - Down 		Dimension	
	Model No.	D	H
	15W	11.8"(D300mm)	5.3"(135mm)
	20W	15.7"(D400mm)	5.3"(135mm)
	25W	18.9"(D480mm)	5.3"(135mm)
	40W	23.6"(D600mm)	5.3"(135mm)
Surface Mounted - Up and Down 		Dimension	
	Model No.	D	H
	50W	18.9"(D480mm)	5.3"(135mm)
	80W	23.6"(D600mm)	5.3"(135mm)

ORDERING INFORMATION

EXAMPLE: DFRD24-40-40901-ACPMK

DFR									
Series	Distribution	Diameter/ Wattage	CCT	CRI	Voltage	Installation	Control	Interior Trim	Exterior Finish
DFR	D Direct	12-15 Ø11.8"/15W 16-20 Ø15.7"/20W 19-25 Ø18.9"/25W 24-40 Ø23.6"/40W	30 3000K 35 3500K 40 4000K	90 90Ra	1 120V- 277V	ACPMK Aircraft Cable Pendant Mount Kits RPMK Rod Pendant Mount Kits SMK Surface Mount Kits	BLANK 0-10V Dimming	BLANK¹ White BK Black GD Golden Optional Finish Colors (Need Additional Charge) ¹	BLANK¹ White BK Black Optional Finish Colors (Need Additional Charge) ¹
	ID Direct and Indirect	19-50 Ø18.9"/50W 24-80 Ø23.6"/80W							

NOTE:

1. Standard Finish is White White and Black Black . Custom finish colors are available at an additional charge. Please contact Customer Service for premium options.

Interior Trim Color Sample¹



ACCESSORIES (ORDERED AND SHIPPED SEPARATELY)



AAL-EBU-AC15D-YYY
Remote 15W LED Emergency
Battery Back-up 120-347VAC.

- NOTE:**
- 1. The 15W EBU supports up to 100W total lighting load.
 - 2. The dimming control wire must be connected .

PERFORMANCE DATA

Lumen values are measured by third party certified laboratories performed in accordance with IESNA LM-79-08 as well as Lighting Facts listed.

Lumen Output

Wattage	Direct Lumen Output	Size	AC Input 120V	CCT	LPW
15W	1280lm	11.8"	0.13A	3000K	85
20W	1700lm	15.7"	0.17A	3000K	85
25W	2100lm	18.9"	0.21A	3000K	85
40W	3400lm	23.6"	0.33A	3000K	85

Wattage	Distribution		Size	AC Input 120V	CCT	LPW
	Direct Lumen Output/ Wattage	Indirect Lumen Output/ Wattage				
50W	2550lm/30W	1700lm/20W	18.9"	0.42A	3000K	85
80W	4250lm/50W	2550lm/30W	23.6"	0.67A	3000K	85

WARRANTY

5 year limited warranty.
Specifications subject to change without notice.