



The Melo Pop Light would greatly create possibilities in the whole commercial area. Multiple beam options, and high visual comfort COB LED. It is now available in pendant and surface mount configurations which offers a beautiful and achitectual solutions.

TECHNICAL DATA

Wattage

4 inch	Selectable 25W/18W/12W
--------	------------------------

Beam Angle	15°, 24°, 36°, 60°
-------------------	--------------------

CRI

Standard	80
----------	----

Optional	90+
----------	-----

CCT	2700K, 3000K, 3500K, 4000K
------------	----------------------------

Driver

Standard	0-10V Dimming, dim to 10%
----------	---------------------------

Optional	0-10V Dimming, dim to 1%
----------	--------------------------

Optional	TRIAC Dimming
----------	---------------

Input Voltage	120-277V, 50/60Hz
----------------------	-------------------

Operating Temp.	-4°F to 77°F (-20°C to 25°C)
------------------------	------------------------------

Certifications	cULus conforms to UL Std. 1598
	Cert. to CSA Std. C22.2 No.250.0

	Suitable for damp locations
--	-----------------------------

	RoHS compliant
--	----------------

Power Factor	>0.9 at full load
---------------------	-------------------


Harmonic Distortion	<20% at full load
----------------------------	-------------------

Projected Lifetime	L70 - 100,000 Hours
---------------------------	---------------------

FEATURES

- **Optical Performance:** COB LED chip with a standard CRI of 80+ and an optional high CRI of 90+, offering a selection of beam angles including 15°, 24°, 36°, and 60°.
- **Mounting Options:** Modular design with pendant or surface mounting.

DIMENSIONS



CANOPY OPTIONS


Flat Canopy For Recessed J-box

If J-box is recessed (3" octagon, 4" octagon and 4" round), a 4.5" flat canopy is provided for mounting to recessed junction box in white or black powder coat painted finish.

Conduit Deep Canopy For Surface Mount J-box

If standard 4" octagonal J-box is surface mounted, a Ø5.97" round x 2.38" deep canopy with conduit cutout is provided for mounting. Conduit cutout canopy has 4 key slots, one in each side, and can be configured to accommodate any ceiling layout using 1/2" or 3/8" conduit. Conduit cutout canopy is provided white and black powder coat painted finish.

Conduit Mounting Example



MOUNTING

Cable Pendant Mount

White/black cable is provided in length specified (4' standard). Installers can cut the cable in the field to desired length.

Notes:

1. For 4", the cable and aircraft cable is combined in one pipe.

MOUNTING LOCATION

Stem Pendant Mount

Ø12/25" steel stem is provided in length specified (4' standard) and is provided in white or black finish.

Surface Mount

Surface mount to rerecessed or surface mounted junction box.

EMERGENCY OPTIONS

Optional high voltage 8W emergency LED driver EM-H08170-LBF can be provided. When AC power fails, it immediately switches to the emergency mode, operating for lighting up to 120 minutes. When AC power is restored, it automatically returns to the charging mode which meets critical life-safety lighting requirements.

For more info or spec sheet, please visit our website or contact sales.

Emergency Lumen Output:




Fixture Efficacy	Output Power 8w
80lm/W	640 Lumens

Canopy With Indicator



PHOTOMETRY

All published luminaire photometric testing performed to IESNA LM-79-08 standards by a NVLAP certified laboratory. IESNA LM-79-08 specifies the entire luminaire as the source resulting in a fixture efficiency of 100%. Results may vary per actual order.



ORDERING INFORMATION

EXAMPLE: MELO04R-SP30901-10D-36-WH

MELO					
1. Series	2. Size	3. Shape	4. Power	5. CCT	6. CRI
MELO	04 4 inch	R Round	SP Wattage Selectable 25W/18W/12W for 4inch	27 2700K 30 3000K 35 3500K 40 4000K	80 80+ CRI (Standard) 90 90+ CRI (Optional)
	7. Voltage	8. Dimming	9. Beam Angle	10. Trim	11. Finish
	1 120-277V	10D Standard 0-10V Dimming, dim to 10% 01D Optional 0-10V Dimming, dim to 1% TRD Optional TRIAC Dimming	15 15° 24 24° 36 36° 60 60°	Ordered and packed separately BLANK Regress Trim <i>Please choose the regress trim in the following accessory table.</i>	WH White BK Black <i>White and black finish are standard. Custom color is available for a premium setup fee. Consult customer service for additional information.</i>

ACCESSORIES (ORDERED SEPARATELY AND FIELD INSTALLED)



MELO-RT-WH

Regress Trim for 4" MELO, white.



MELO-RT-BK

Regress Trim for 4" MELO, black.




EBU-H08170

8W Emergency Battery Back-up (ordered separately and field installed).

Notes:


1. Emergency battery back-up is for ambient temperatures of 32°F - 77°F (0 °C - 25°C).

For Recessed Junction Box



MELO-PMK-AC-RM-4-4FT-WH

Aircraft cable mount for 4" MELO, 4ft long cable, white (recessed junction box).



MELO-PMK-RS-RM-4-4FT-WH


Rigid stem mount for 4" MELO, 4ft long stem, white (recessed junction box).



MELO-SMK-SM-RM-4-WH


Surface mount for 4" MELO, white (recessed junction box).

For Surface Mounted Junction Box



MELO-PMK-AC-SM-4-4FT-WH

Aircraft cable mount for 4" MELO, 4ft long cable, white (surface mounted junction box).



MELO-PMK-RS-SM-4-4FT-WH

Rigid stem mount for 4" MELO, 4ft long stem, white (surface mounted junction box).



MELO-SMK-SM-SM-4-WH

Surface mount for 4" MELO, white (surface mounted junction box).

PERFORMANCE DATA

Lumen values are measured by third party certified laboratories performed in accordance with IESNA LM-79-08 as well as Lighting Facts listed.

Diameters	4inch
Wattage	25W/18W/12W
Voltage	120-277V
Efficacy @3000K	2600lm@25W
Installation	Pendant / Surface Mount
Controls (Optional)	Emergency Battery Back-up

WARRANTY

5 years limited warranty.

Specifications subject to change without notice.

Ref#: 20250929