

VEGA DC SMALL LED LIGHT

Wall Washer



The VEGA DC Small LED RGBW Wall Washer is DC 24V, designed for exterior landscape and facade lighting. Choose from a selection of available distribution / beam angles, customizing the perfect solution for grazing / wall washing. A range of white CCT (monochrome) is available to choose from. Chosen white CCT as well as chosen beam angle will be set at the factory. The luminaire body utilizes #6063 aluminum alloy molding, with an anodizing surface treatment. The lamp lens is high strength glass.

TECHNICAL DATA


Wattage	18W
CRI	70
CCT	2200K, 2700K, 3000K, 3500K, 4000K Red, Green, Blue
Input Voltage	24V DC, 50/60Hz
Driver	On/Off
Operating Temp.	-40°F to 104°F (-40°C to 40°C)
Certifications	cETL listed RoHS compliant Suitable for wet locations
Power Factor	>0.9
Projected Lifetime	L70 - 50,000 Hours
IP Rating	IP66

FEATURES

- **Versatile Performance Options:** Offers various light distributions and multiple monochrome color options.
- **Durable Material Construction:** Features a robust housing made from low copper content extruded aluminum for long-lasting performance.

SPECIFICATION

Top View



Front and Side View



Input Cable

ORDERING INFORMATION

EXAMPLE: VEGA-1835-24V-20-BK

VEGA						
Series	Wattage	CCT and Color	Voltage	Controls	Beaming Angle	Finish
VEGA	18 18W	22 2200K 30 3000K 35 3500K 40 4000K R Red G Green B Blue	24V 24V DC	BLANK On/Off	20 20° 30 30° 45 45° 15x30 15°x30° 20x30 20°x30° 25x50 25°x50° 25x45 25°x45°	BK ² Black GY Grey

NOTE:

- Maximum 8 luminaires can be connected per series.
- Standard Finish is Black. Custom colors might be available for an additional fee. Please check with Customer Service for more information.

ACCESSORIES (ORDERED SEPARATELY AND FIELD INSTALLED)



LCB-2PIN

2-pin leader cable with female plug for DC power lead wiring.



XLG-150-24¹

150W ON/OFF LED driver
input voltage: AC100-305V,
output voltage: 24V DC.

XLG-100-24¹

100W ON/OFF LED driver
input voltage: AC100-305V,
output voltage: 24V DC.

NOTE:

- 1. Total luminaires wattage can exceed the driver's wattage.

PERFORMANCE DATA

Lumen values are measured by third party certified laboratories performed in accordance with IESNA LM-79-08 as well as Lighting Facts listed.

Wattage	Lumen Output	AC Input 120V	CCT	LPW
18W	1530lm	0.15A	3000K	85

WARRANTY

5 years limited warranty.
Specifications subject to change without notice.