




3W LED Step/Wall Lights are available in a vertical configuration for mounting into a junction box. For poured concrete and masonry installations. For indoor and protected outdoor use.

TECHNICAL DATA

Wattage	3W
CCT	3000K
Dimming	Non-Dimming
CRI	80
Input Voltage	120V, 50/60Hz
Projected Lifetime	L70-100,000 Hours
Operating Temp.	-13°F to 95°F (-25°C to 35°C)
Certifications	ETL listed Suitable for wet locations RoHS compliant
Power Factor	>0.87

SPECIFICATION

Dimension



ORDERING INFORMATION

EXAMPLE:VMSL03304-BK

Model	Wattage	CCT	Voltage	Controls	Finish
VMSL	03 3W	30 3000K	4 120V	BLANK On/Off	BK ¹ Black ¹

NOTE:

1. Black finish is standard. Custom finish colors are available at an additional charge. Please contact Customer Service for premium options.
2. Minimum order required, please contact Customer Service for additional information.


PERFORMANCE DATA

Lumen values are measured by third party certified laboratories performed in accordance with IESNA LM-79-08 as well as Lighting Facts listed.

Wattage	Lumen Output	AC Input 120V	CCT	CRI
3W	80lm	0.03A	3000K	80

PHOTOMETRY

All published luminaire photometric testing performed to IESNA LM-79-08 standards by a NVLAP certified laboratory. IESNA LM-79-08 specifies the entire luminaire as the source resulting in a fixture efficiency of 100%. Result may vary per actual order.



BUG RATING TABLE

Performed to IESNA LM-79-08 standards by a NVLAP accredited laboratory.

Model	BUG Rating
VMSL03304-BK	B0-U1-G0

WARRANTY

5 year limited warranty.

Specifications subject to change without notice.