


5" CORLA DOWNLIGHT

Deep Anti-glare Series



The Corla Downlight System revolutionizes interior lighting through modular adaptability. Featuring precision-engineered optics and adjustable configurations, the system delivers exceptional light quality with superior optical control.

TECHNICAL DATA

Wattage	30W, 35W (single module)
CRI	90, SDCM<3
CCT	2700K, 3000K, 3500K, 4000K Dim to Warm: 2000K-3000K
Dimming	Triac dimming (1%-100%) 0-10V dimming (3%-100%)
Input Voltage	120-277V, 50/60Hz
Projected Lifetime	L80-50,000 hours
Working Temperature	-4°F to 104°F (-20°C to 40°C)
Certifications	ETL Listed to US and Canadian standards Suitable for damp locations RoHS compliant
Power Factor	>0.9 at full load
Harmonic Distortion	<20% at full load

FEATURES

- **Super Modular Design:** 2 mounting trims and tool-free interchangeable components.
- **Precise Light Control:** 4 beam angles (15°/24°/38°/55°), URG<9, anti-glare accessories, and a 48° cutoff angle.
- **Versatile Project Adaptability:** supports general lighting, spot/flood and accent lighting.
- **Optimized Thermal Performance:** guarantees long-term durability and consistent luminous performance.

5" CORLA DOWNLIGHT


Deep Anti-glare Series

SPECIFICATION

LED Module



4-1/4"
(108mm)




Ø3-35/64"
(Ø90mm)

Trims



7-57/64"
(200.5mm)



Ø5-33/64"
(Ø140mm)




4-59/64" (Ø125mm)


Round Fixed



7-57/64"
(200.5mm)





5-33/64"
(Ø140mm)



4-59/64" *4-59/64"
(125x125mm)


Square Fixed

Remodel Mounted Driver



7-43/64"
(195mm)

2-23/64"
(59.8mm)



1-15/32"
(37.3mm)

5" CORLA DOWNLIGHT

Deep Anti-glare Series

ORDERING INFORMATION

EXAMPLE

COR	05	30	35	90	1	XD	38
1	2	3	4	5	6	7	8

1. Series

- ☒ **COR**- Corla LED Module

2. Size

- ☐ **05** - 5 inch Module

3. Wattage (single module)

- ☐ **30** - 30W ☐ **35** - 35W

4. CCT

- ☐ **27**- 2700K ☐ **30**- 3000K
☐ **35**- 3500K ☐ **40**- 4000K
☐ **DTW**- 2000K-3000K dim to warm

5. CRI

- ☐ **90** - 90Ra

6. Voltage

- ☐ **1** - 120-277V

7. Dimming

- ☐ **XD** - 0-10V/Triac Dimming

NOTE:

1. Triac dimming only works on 120VAC.

8. Beaming Angle

- ☐ **15** - 15° ☐ **24** - 24°
☐ **38** - 38° ☐ **55** - 55°

Mounting Accessory Options

- ☐ **RIP-55135**

- ☐ **RIP-70145**

New construction pre-mounting plate for Corla Downlight.

NOTE:

1. Please refer to the Selection Guide to select proper plate.

Trim Options

- ☐ **CORD05-R-DL-WH**

Deep Anti-glare series, round trim, fixed, white trim



- ☐ **CORD05-S-DL-WH**

Deep Anti-glare series, square trim, fixed, white trim



NOTE:

1. White trim is standard finish. Custom colors are available at an additional fee.

Optical Accessory Options

- ☐ **COR05-HCB**

Honeycomb Filter



- ☐ **COR05-BSL**

Beam Soft Lens



Emergency Battery Back-up Options

- ☐ **AAL-EBU-AC08D-YYY**

Remote 8W LED Emergency Battery Back-up 120-347VAC

- ☐ **AAL-EBU-AC15D-YYY**

Remote 15W LED Emergency Battery Back-up 120-347VAC

- ☐ **AAL-EBU-AC25D-YYY**

Remote 25W LED Emergency Battery Back-up 120-347VAC



NOTE:

1. A single EBU can power multiple light fixtures. The 8W EBU supports up to 60W total lighting load, 15W EBU supports up to 100W total lighting load, while the 25W EBU supports up to 150W total lighting load.
2. The dimming control wire is optional when the combined power of all connected lights is lower than the EBU's rated power.
3. The dimming control wire must be connected when the total power of all connected lights exceeds the EBU's rated capacity.

ROUGH-IN PLATE SELECTION GUIDE

To ensure a proper fit, select the correct rough-in plate by matching it to your fixture's cutout size.

Follow the 2 steps below:


Step 1. Identify the Cutout Size: Locate the Corla Downlight model in the table below and note its required cutout dimension.

Step 2. Match the Plate: Using the diagram that follows, find the rough-in plate part# that corresponds to the cutout size you identified in Step 1.

Corla Downlight Cutout Dimension Table

Model	Hotel	Residential	Commercial	Deep Anti-Glare	Wall Washer
COR02	Ø2.17"(55mm)	Ø2.17"(55mm)	Ø2.56"(65mm)	/	/
COR03	Ø2.95"(75mm)	Ø2.95"(75mm), Ø2.68"(68mm)	Ø3.15"(80mm)	Ø2.95"(75mm)	Ø2.95"(75mm)
COR04	Ø3.94"(100mm)	Ø4.53"(115mm), Ø3.94"(100mm)	Ø3.74"(95mm)	Ø3.94"(100mm)	/
COR05	Ø4.92"(125mm), Ø4.8"(122mm)	Ø4.33"(110mm), Ø4.92"(125mm) Ø5.12"(130mm), Ø5.31"(135mm)	Ø4.53"(115mm)	Ø4.92"(125mm)	/

Rough-in Plate




Part#

RIP-55135

New construction pre-mounting plate for Corla Downlight.

Compatible cutouts:

Ø2.17"(Ø55mm)
Ø2.68"(Ø68mm)
Ø3.15"(Ø80mm)
Ø3.74"(Ø95mm)
Ø4.53"(Ø115mm)
Ø4.92"(Ø125mm)
Ø5.31"(Ø135mm)



Part#

RIP-70145

New construction pre-mounting plate for Corla Downlight.

Compatible cutouts:

Ø2.76"(Ø70mm)
Ø2.95"(Ø75mm)
Ø3.94"(Ø100mm)
Ø4.33"(Ø110mm)
Ø4.8"(Ø122mm)
Ø5.12"(Ø130mm)
Ø5.71"(Ø145mm)


5" CORLA DOWNLIGHT

Deep Anti-glare Series


PHOTOMETRY

All published luminaire photometric testing performed to IESNA LM-79-08 standards by a NVLAP certified laboratory. IESNA LM-79-08 specifies the entire luminaire as the source resulting in a fixture efficiency of 100%. Results may vary per actual order.

30W



35W



Above test data is based on **Round** trim with 3000K 90CRI LED.

PERFORMANCE DATA

POWER	CCT	CRI	BEAM OPTIC	LUMENS (lm)	EFFICACY (lm/W)	MAX CANDELA (cd)
30W	3000K	90	15°	2525	91	17219
			24°	2604	95	12561
			38°	2557	92	6171
			55°	2412	88	4106
35W	3000K	90	15°	2852	89	19437
			24°	2891	90	13942
			38°	2916	91	7043
			55°	2797	87	4753

Above test data is based on **Round** trim with 3000K 90CRI LED.

LUMEN MULTIPLIERS

CCT	MULTIPLIER
2700K	0.95
3000K	1.00
3500K	1.04
4000K	1.06