




The NOVA LED Commercial Downlights are available in 4inch, 6inch, 8inch and 10inch with up to 60W. The integral junction box and choice of trim feature, adds to the flexibility of this downlight. Butterfly clips make for easy-fit installation whether new construction or retrofit. The integral junction box eliminates the need for a traditional recessed housing and the complete fixture mounts directly into the ceiling. It is suitable for commercial and public places and elegantly decorates the ambience, such as shopping mall, hospital, airport, hotel lobby etc.

TECHNICAL DATA

Wattage

20SP	Selectable 10W/15W/20W
40SP	Selectable 27W/34W/40W
60SP	Selectable 40W/50W/60W
CCT	Selectable 3000K/3500K/4000K default setting: 4000K

Driver	1-10V dimming is standard
CRI	80

Input Voltage

20SP/40SP	120-347V, 50/60Hz (dim to 10%)
60SP	120-277V, 50/60Hz (dim to 1%)

Projected Lifetime	L70-100,000 Hours
--------------------	-------------------

Operating Temp.	-4°F to 104°F (-20°C to 40°C)
-----------------	-------------------------------

Certifications	cULus conforms to UL Std. 1598 Cert. to CSA Std. C22.2 No.250.0 RoHS compliant Suitable for damp locations
----------------	---

Power Factor	>0.9 at full load
--------------	-------------------

Harmonic Distortion	<20% at full load
---------------------	-------------------

FEATURES

- 4inch, 6inch, 8inch and 10inch trim size options.
- Various changable trim design.
- Available in round, square, round wall wash and square wall wash trims.
- Twist-lock modular design.
- Integrated J-box for direct wire, eliminated recessed can.
- CCT and wattage selectable.
- New construction frame kit available.

PERFORMANCE DATA

Lumen values are measured by third party certified laboratories performed in accordance with IESNA LM-79-08 as well as Lighting Facts listed.

Wattage	Lumen Output			Type
	High	Medium	Low	
Maximum 20W	20W, 1500lm (75lm/W)	15W, 1170lm (78lm/W)	10W, 800lm/W (80lm/W)	NON-IC
Maximum 40W	40W, 3200lm (80lm/W)	34W, 2890lm (85lm/W)	27W, 2430lm (90lm/W)	NON-IC
Maximum 60W	60W, 6180lm (103lm/W)	50W, 5300lm (106lm/W)	40W, 4360lm (109lm/W)	NON-IC

NOTE:

All efficacy is subject to 4000K which has $\pm 5\%$ base on different CCT and trims. Check the IES file to gain the accurate data.

ORDERING INFORMATION

Engine

EXAMPLE: NOVA-20SPSW8

NOVA					
1. Series	2. Wattage	3. CCT	4. Voltage	5. Trim	6. Options
NOVA	20SP Selectable 10W/15W/20W ¹ 40SP Selectable 27W/34W/40W ¹ 60SP Selectable 40W/50W/60W ¹	SW Selectable 3000K 3500K 4000K ²	For 20SP and 40SP 8 120-347V, dim to 10% For 60SP 1 120-277V, dim to 1% <i>*Tested Dimmers:</i> Lutron® Diva-Dvtv, Leviton® IP-710-DL.	BLANK None <i>The following options need to be ordered separately. Please check details in the following trim ordering guide.</i> Round Trim Round Wall Wash Trim Square Trim Square Wall Wash Trim	BLANK None <i>The following options need to be ordered separately. Please check details in the following accessory table.</i> Round Pre-mounting Plate Square Pre-mounting Plate Emergency Battery Back-up

NOTE:

1. 20W, 40W and 60W are default setting.
2. 4000K is default setting.

TRIM ORDERING GUIDE

Different trims need to be ordered separately and field installed.

Round Trim

EXAMPLE: NOVA4-RT-WH

NOVA			
1. Series	2. Size	3. Shape	4. Finish
NOVA	4 4" Cutout: 4.7"-5.2" <i>*Not available for 60SP.</i> 6 6" Cutout: 6"-7.3" 8 8" Cutout: 7.4"-8.9" 10 10" Cutout: 9.5"-10.8"	RT Round Trim	WH White Ring Reflector is aluminum natural color anodizing treatment. MT Metal Ring Reflector is aluminum natural color anodizing treatment. <i>*Metal color is not available for 10".</i> BK Black ring and reflector <i>*Black is not available for 10".</i> RS Rose ring and reflector <i>*Rose is not available for 8" and 10".</i>

Square Trim

EXAMPLE: NOVA4-ST-WH

NOVA			
1. Series	2. Size	3. Shape	4. Finish
NOVA	4 4" Cutout: 5.3"-6" <i>*Not available for 60SP.</i> 6 6" Cutout: 6"-7.3"	ST Square Trim	WH White Ring Reflector is aluminum natural color anodizing treatment.

TRIM ORDERING GUIDE

Different trims need to be ordered separately and field installed.

Round Wall Wash Trim

EXAMPLE: NOVA4-RWWT-WH

NOVA			
1. Series	2. Size	3. Shape	4. Finish
NOVA	4 4" Cutout: 5.3"-6" 6 6" Cutout: 6"-7.3"	RWWT Round Wall Wash Trim 10°-20° tilt <i>*Not available for 60SP.</i>	WH White Ring Reflector is aluminum natural color anodizing treatment.

Square Wall Wash Trim

EXAMPLE: NOVA4-SWWT-WH

NOVA			
1. Series	2. Size	3. Shape	4. Finish
NOVA	4 4" Cutout: 5.3"-6" 6 6" Cutout: 6"-7.3"	SWWT Square Wall Wash Trim 10°-20° tilt <i>*Not available for 60SP.</i>	WH White Ring Reflector is aluminum natural color anodizing treatment.

ACCESSORIES (ORDERED AND SHIPPED SEPARATELY)



NOVA-3/8-R-RIP

New Construction.
Round Pre-mounting Plate.
Opening for 3" to 8".



NOVA-4/6-S-RIP

New Construction.
Square Pre-mounting Plate.
Opening for 4" to 6".



AAL-EBU-AC08D-YYY¹

Remote 8W LED Emergency Battery
Back-up 120-347VAC.

AAL-EBU-AC25D-YYY¹

Remote 25W LED Emergency Battery
Back-up 120-347VAC.


NOTE:

1. The 8W EBU supports up to 60W total lighting load. The 25W EBU supports up to 150W total lighting load. The dimming control wire must be connected. Emergency battery backup operates within ambient temperatures of 32°F to 95°F (0°C to 35°C).

DIMENSION


Engine

20SP




10W NON-IC
15W NON-IC
20W NON-IC

40SP



40W NON-IC


60SP




60W NON-IC

Fixture


20SP – Round Trim




4" Round Trim



6" Round Trim




8" Round Trim




10" Round Trim

20SP – Round Wall Wash Trim




4" Round
Wall Wash Trim




6" Round
Wall Wash Trim

20SP – Square Wall Wash Trim




4" Square
Wall Wash Trim




6" Square
Wall Wash Trim

20SP – Square Trim



4" Square Trim




6" Square Trim


DIMENSION

Fixture


40SP – Round Trim




4" Round Trim



6" Round Trim




8" Round Trim




10" Round Trim

40SP – Round Wall Wash Trim




4" Round Wall Wash Trim




6" Round Wall Wash Trim

40SP – Square Wall Wash Trim




4" Square Wall Wash Trim




6" Square Wall Wash Trim

40SP – Square Trim




4" Square Trim




6" Square Trim

60SP – Square Trim




6" Square Trim


60SP – Round Trim



6" Round Trim



8" Round Trim



10" Round Trim

DIMENSION

Trim

Round Trims

4"

Cut-hole Dimensions: 4.7"-5.2"





White Ring

Metal Trim

Rose Trim

Black Trim

Metal Reflector



6"

Cut-hole Dimensions: 6"-7.3"





White Ring

Metal Trim

Rose Trim

Black Trim

Metal Reflector



8"

Cut-hole Dimensions: 7.4"-8.9"





White Ring

Metal Trim

Black Trim

Metal Reflector





10"

Cut-hole Dimensions: 9.5"-10.8"



White Ring

Metal Reflector



Round Wall Wash Trims



4"

Cut-hole Dimensions: 5.3"-6"



White Ring

Metal Reflector





6"

Cut-hole Dimensions: 6"-7.3"



White Ring

Metal Reflector




DIMENSION

Trim

Square Trims


4"

Cut-hole Dimensions: 5.3"-6"



6"


Cut-hole Dimensions: 6"-7.3"



Square Wall Wash Trims


4"

Cut-hole Dimensions: 5.3"-6"



6"

Cut-hole Dimensions: 6"-7.3"




PHOTOMETRY

All published luminaire photometric testing performed to IESNA LM-79-08 standards by a NVLAP certified laboratory. IESNA LM-79-08 specifies the entire luminaire as the source resulting in a fixture efficiency of 100%. Results may vary per actual order.

6" 20W Square Trim


Lumens: 1515.4lm
 Watts: 20 W
 LPW: 75.77lm/W
 CCT: 4000K



AVERAGE BEAM ANGLE(50%): 76.6 DEG

6" 20W Square Wall Wash


Lumens: 1590.6lm
 Watts: 20 W
 LPW: 79.53lm/W
 CCT: 4000K



AVERAGE BEAM ANGLE(50%): 71.0 DEG

6" 40W Round Trim


Lumens: 3328.0lm
 Watts: 40 W
 LPW: 83.2lm/W
 CCT: 4000K



AVERAGE BEAM ANGLE(50%): 57.4 DEG

6" 40W Round Wall Wash


Lumens: 2949.1lm
 Watts: 40 W
 LPW: 73.73lm/W
 CCT: 3000K



AVERAGE BEAM ANGLE(50%): 71.0 DEG

6" 60W Round Trim

Lumens: 6080.5lm
 Watts: 60 W
 LPW: 105.62lm/W
 CCT: 4000K



AVERAGE BEAM ANGLE(50%): 56.9 DEG

WARRANTY

5 years limited warranty.

Specifications subject to change without notice.