DEEP FOCUS ROUND LIGHT

ABOVE ALL
www.AboveAllLighting.com





Rod
Pendant Mount



Aircraft Cable
Pendant Mount



Surface
Mount

FEATURES

- Fixtures in diameters from 11.8" through 23.6".
- Deep recessed light source design.
- Pendant or surface mounted.
- Direct and indirect lighting for option.

The Deep Focus Round Light offers the Focus family more choices. Fixture comes in diameters from 11.8" through 23.6". Deep recessed light source design achieving perfect glare control. Flexible installations come in pendant and surface mounted. Direct and indirect lighting for option. The Deep Focus Light is perfect for both commercial and residential applications.

TECHNICAL DATA

Wattage	
Direct	15W, 20W, 25W, 40W
Direct and Indirect	50W, 80W
CCT	3000K, 3500K, 4000K
Driver	0-10V Dimming standard
CRI	90Ra
Input Voltage	120-277V, 50/60Hz
Projected Lifetime	L70-100,000 Hours
Operating Temp.	-4°F to 104°F (-20°C to 40°C)
Certifications	cETLus conforms to UL Std. 1598
	Cert. to CSA Std. C22.2 No.250.0
	RoHS compliant
	Suitable for damp locations
Power Factor	>0.9 at full load
Harmonic Distortion	<20% at full load

PERFORMANCE DATA

Watt.	Direct Lumen Output/ Wattage	Indirect Lumen Output/ Wattage	LPW
15W	1280lm/15W	–	85
20W	1700lm/20W	–	85
25W	2100lm/25W	–	85
40W	3400lm/40W	–	85
50W	2550lm/30W	1700lm/20W	85
80W	4250lm/50W	2550lm/30W	85

**For complete performance data, please refer to the detailed table on page 2.*

©2026 ABOVE ALL Lighting, Inc. All rights reserved.

PERFORMANCE DATA

Lumen values are measured by third party certified laboratories performed in accordance with IESNA LM-79-08 as well as Lighting Facts listed.

Lumen Output

Wattage	Direct Lumen Output/Wattage	Indirect Lumen Output/Wattage	Size	AC Input 120V	CCT	LPW
15W	1280lm/15W	–	11.8"	0.13A	3000K	85
20W	1700lm/20W	–	15.7"	0.17A	3000K	85
25W	2100lm/25W	–	18.9"	0.21A	3000K	85
40W	3400lm/40W	–	23.6"	0.33A	3000K	85
50W	2550lm/30W	1700lm/20W	18.9"	0.42A	3000K	85
80W	4250lm/50W	2550lm/30W	23.6"	0.67A	3000K	85

ORDERING INFORMATION

EXAMPLE: DFRD24-40-40901-ACPMK

DFR									
Series	**Distribution**	**Diameter/ Wattage**	**CCT**	**CRI**	**Voltage**	**Installation**	**Control**	**Interior Trim**	**Exterior Finish**
DFR	**D** Direct	**12-15** Ø11.8"/15W[2] **16-20** Ø15.7"/20W **19-25** Ø18.9"/25W **24-40** Ø23.6"/40W	**30** 3000K **35** 3500K **40** 4000K	**90** 90Ra	**1** 120V-277V	**ACPMK** Aircraft Cable Pendant Mount Kits **RPMK** Rod Pendant Mount Kits **SMK** Surface Mount Kits	**BLANK** 0-10V Dimming	**BLANK**[1] White **BK** Black **Optional Finish Colors** *The following colors are available at an additional charge.*[1] **GD** Golden **CC** Custom Colors *(Provide RAL#)*	**BLANK**[1] White **BK** Black **Optional Finish Colors** *The following colors are available at an additional charge.*[1] **CC** Custom Colors *(Provide RAL#)*
	ID Direct and Indirect	**19-50** Ø18.9"/50W **24-80** Ø23.6"/80W							

©2026 ABOVE ALL Lighting, Inc. All rights reserved.

ORDERING INFORMATION

NOTE:

1. Standard Finish is White White and Black Black . Custom finish colors are available at an additional charge. Please contact Customer Service for premium options.
2. The Ø11.8"/15W model is subject to a MOQ requirement.

Interior Trim Color Sample[1]



ACCESSORIES (ORDERED AND SHIPPED SEPARATELY)



AAL-EBU-AC15D-YYY
Remote 15W LED Emergency
Battery Back-up 120-347VAC.

NOTE:

1. The 15W EBU supports up to 100W total lighting load.
2. The dimming control wire must be connected.
3. The EBU is Title 20 compliant.

©2026 ABOVE ALL Lighting, Inc. All rights reserved.

SPECIFICATION

Dimension

Aircraft Cable and Wire Cord Length: 59" .
Pendant Rod Length: 47.2".

Suspended - Down		Dimension			
	**Wattage**	**D**	**H**	**A**	**B**
	15W	11.8"	4.0"	10.0"	1.38"
	20W	15.7"	4.0"	10.0"	1.38"
	25W	18.9"	4.0"	10.0"	1.38"
	40W	23.6"	4.0"	10.0"	1.38"
Suspended - Up and Down		**Dimension**			
	**Wattage**	**D**	**H**	**A**	**B**
	50W	18.9"	4.0"	10.0"	1.38"
	80W	23.6"	4.0"	10.0"	1.38"
Stem - Down		**Dimension**			
	**Wattage**	**D**	**H**	**A**	**B**
	15W	11.8"	4.0"	5.0"	1.4"
	20W	15.7"	4.0"	5.0"	1.4"
	25W	18.9"	4.0"	5.0"	1.4"
	40W	23.6"	4.0"	5.0"	1.4"
Stem - Up and Down		**Dimension**			
	**Wattage**	**D**	**H**	**A**	**B**
	50W	18.9"	4.0"	5.0"	1.4"
	80W	23.6"	4.0"	5.0"	1.4"

©2026 ABOVE ALL Lighting, Inc. All rights reserved.

Surface Mounted - Down		Dimension	
	**Wattage**	**D**	**H**
	15W	11.8"	5.3"
	20W	15.7"	5.3"
	25W	18.9"	5.3"
	40W	23.6"	5.3"
Surface Mounted - Up and Down		**Dimension**	
	**Wattage**	**D**	**H**
	50W	18.9"	5.3"
	80W	23.6"	5.3"

WARRANTY

5 year limited warranty.

Specifications subject to change without notice.

©2026 ABOVE ALL Lighting, Inc. All rights reserved.